

Everlast 1 Winter Grade Low Temp Multi-Purpose

Description

Everlast 1 Winter Grade is a low temp synthetic lubricant for use in valves carrying aliphatic hydrocarbon liquids and gasses, including kerosene, fuel oils, crude distillates (sweet or sour), water, condensate, LPG systems, dilute acids and caustics. It is waterproof and has excellent resistance to oxidation.

Applications

Designed for low torque valve operation in cold environments. For use in gate, plug and ball valves. Suitable for use in hydrocarbon gasses.

DO NOT use in oxygen service.

Features

- Water resistant
- Fully additive treated
- High metal adhesion
- Excellent corrosion resistance
- Inhibited for H₂S

Physical Properties

- Consistency, Cone Penetration (D-217) 220-300
- Dropping Point, °F (D-566) none
- Oil Separation, % wt. loss (D-1742) 5 max
- Oxidation Stability (D-942) 10 max
- Rust Preventive Test (D-1743) pass
- Temperature range: Winter Grade -40° to 620°F, Arctic Grade -70° to 620°F
- Color - brown
- Type Oil - synthetic
- Corrosive Inhibitor - Imidazoline Derivative
- EP Additive - Diester Type

Product Codes

- **Arctic Grade - EV1AG**
- **Winter Grade - EV1WG**